

SERIE S

| TECHNICAL DATA | S10 | S16 |
|----------------------------|------------------------|------------------------|
| Rated resistive current | 10 A | 16 A (n.a.) |
| Rated motor current | 4 A | 10 A (n.c.) |
| Rated voltage | 250 V A.C. | 250 V A.C. |
| Max operating temperature | 125° C | 125° C |
| Operating force | 3,75 ± 0,75 N | 6 ± 1 N |
| Mechanical life | > 10 ⁵ | > 10 ⁵ |
| Electrical life | > 50 x 10 ³ | > 50 x 10 ³ |
| Duty type | +++ freq. | +++ freq. |
| Contact gap | < 3 mm | < 3 mm |
| Proof Tracking Index (PTI) | > 250 V | > 250 V |
| Terminals | 6,3 x 0,8 mm | 6,3 x 0,8 mm |



SERIE M5

| TECHNICAL DATA | M5 / M5S |
|----------------------------|------------------------|
| Rated resistive current | 5 A |
| Rated motor current | 1,5 A |
| Rated voltage | 250 V A.C. |
| Max operating temperature | 125° C |
| Operating force | 1,5 ± 0,5 N |
| Mechanical life | > 10 ⁵ |
| Electrical life | > 50 x 10 ³ |
| Duty type | +++ freq. |
| Contact gap | < 3 mm |
| Proof Tracking Index (PTI) | > 250 V |
| Terminals | 6,3 x 0,8 mm |

SERIE N

| TECHNICAL DATA | N8 | N16 |
|----------------------------|------------------------|------------------------|
| Rated resistive current | 8 A | 16 A (n.a.) |
| Rated motor current | 2 A | 10 A (n.c.) |
| Rated voltage | 250 V A.C. | 250 V A.C. |
| Max operating temperature | 125° C | 125° C |
| Operating force | 3,2 ± 0,7 N | 6 ± 1 N |
| Mechanical life | > 10 ⁵ | > 10 ⁵ |
| Electrical life | > 50 x 10 ³ | > 50 x 10 ³ |
| Duty type | +++ freq. | +++ freq. |
| Contact gap | < 3 mm | < 3 mm |
| Proof Tracking Index (PTI) | > 250 V | > 250 V |
| Terminals | 6,3 x 0,8 mm | 6,3 x 0,8 mm |

